

2019 3

_____ ()

190

OCC ATS

		1) 1			
		2) 50Hz			
		3)			
		1			
		12kg/M			
		2			/
		3			
		50Hz			
		30 50Hz		10V	
		3.			
		1)	1		1
			1		
		2)		1	1
			1		
		3)			
		LED		20mA	
				120mA	
				DC39.5V	
				<8w	
			AC	43V-52V	
				3	
				3	
				TB/T2353-93	
				TB2081-89	
				15Kg	
		4.			
		1)	ZD J 9		
			2		
			2.0A		
		Ø	AC380V		
		DC220V			
		Ø	28 2KN		
		Ø	54		
		Ø	5. 8s		
		Ø	2.0A		
		2			
		5.			
		1)	1		
		2)			

		3) 6. [2016]147 TJ/DW188-2016 1) 1 2) 3) -SICAS / / / 4 CAN CAN X 18	
--	--	---	--

[illegible]

- d) 4
- e)

10.

- 1) 1

2)

- a) DC220V AC380V AC220V AC110V DC24V DC12V
DC5V

b)

- c) 5kVA

d)

	AC220V±10V	2A
50HZ	AC220V±6.6V	5.45A
50HZ	AC110V±3.3V	7.27A
	AC220V±10V	1A
	AC220V±10V	5A
	AC220V	5A
	DC220V -10 +20V	16A×
	AC380V	5A
	DC24V 0 +2V	10A
	DC24V 60V±5V	2A
50Hz	AC220V±10V	2A
50HZ	AC110V±5V	2A
	AC24V±3V	5A
	AC24V±3V	1A
	DC24-48V	2A

2 4.5V
10A

< 50mV
< 10mV

12.

1) 1

2)

1

13.

1) 1

1

2) ZP43V

ZP47

ZP43V

3)

14. AP

1) AP 1

2)

AP

15.

1)

2)

16.

		7 8	900mm* 400mm* 1800mm 1	
3		1 4 2 1	1m 0.5m 1m 0.5m 1m 0.5m 0.3m 0.8m	1