
AFC

30-50

196 18m 12m

1		1. i7-8700 2. NVIDIA GeForce GTX1070-8G GDDR5 3. 16GB DDR4 2666MHz 4. 256GB SSD+2TB 7200RBM dows 5. Windows10& Office 6. 24	5
2	VR		4

		9. POR	
3	LED	1. * (mm) 1021.98*576.57mm 2. 3065.94*1153.14mm 3. LED 4. 1920*1080 5. 500cd/m2 6. 3.5mm 7. 16 9 8. 4500 1 9. RS232 10. M* N M/N=6 11. 12. 16.7M 13. 178 /178 H\V 14. 180w 15. 6ms 16. / 0 60 /10%-95% 17. 18. 19. VGA 1 D-sub15 1920 1200/60HZ 20. HDMI 1 (HDMI) 1920 1080/60HZ 21. DVI 1 (DVI) 1920 1080/60HZ 22. BNC1 2 (BNC) 23. USB 1 USB-A 24. 6 25. 3D LED 6 92% 26. 178 () 27. 365 8 28. 29.	1
4		LED	1
5		1 1800*600*600MM 2. SPCC 1.2mm 2.0mm 3. 19 4. 6 10A 5. 2	1
6		1. 2. 48 3. 10/100/1000Mbps	1

		4. 78MPPS 5. 100-240V 9. 442(W) 310(D) 43.6(H)mm 10.PoE 11.Console 1	
7		1. 50Hz-20kHz 2. 1 8 2 3 3. 4. 120W 5. 8 6. 92dB/1W/1M 7. 102dB 8. 1.8KHz 9. 10. 11. 12. 10CM 2 M8 13. 450 240 270mm mm CAD	2
8		1. INPUT 4 MIC 4, 2. 2 3. 20Hz-20KHz 50Hz-18KHz 4. 10KHz 12dB 100Hz 12dB 5. 5mV 200mV 6. 2 250W 7. 0.03% 8. 85dB A 9. AC 220V/50Hz 10. 350W 11. 280 355 105 mm 1 DC6V	1

		4 8	
9		740 790MHz FM 50MHz 0.005% 250KHz 100dB 45KHz 80 1800Hz(3dB) >105dB 0.5% -10 --40 110MHz, 10.7MHz BNC/50 12dB V 20dB SINAD 75 dB LCD +10 dBV 1/4 30mW 3mW LCD -60 dB AA 30mW 10 3mW 15 PLL UHF 740 790MHz 19 ELA AF RF LCD -	1

100

80

UHF
200

		0.5W	
	4	/ :0-40 (32-104)/20-80%()	
		/ :-10-+60 (-4-140)/20-80%()	
	5.	365×96.2×252mm	
	1.	C/S	
	2.		
	1		
	2		
		/	
	3		

- 1) Lua
- 2)
- 3)
- 4) Flash VR Flash
Flash ActionScript Flash
- 5)
- 6)
- 7)
- 8)
- 9) Bloom HDR

		34)			
		35)			
		36)			
		37)			
		38)BS		IE	
		39)			
		40)			
		41)			
		42)			
		43)			
		44)			
		45)			
		46)			
		47)	EXE		
			.exe .vrp		
		48)			
			VC		
		49)			
		50)			
		51)			
			VC VB DELPHI C# VS.NET		

		52) 3dsmax 3ds Max 3ds Max 3dsmax 3dsmax 3dsmax Forest Reactor	
17	AFC	1. 3D 8 2 2 2. 3. 360 4. 5. SC 6. 7. AFC SC 8.SC BOM TVM AG 9.SC AG 10. C/S	10 1
18		5 / 3	2

		(W) 12000 (W) 4000 (W) 13200 (W) 4162 (W) 2100 (dB(A) 54 (dB(A) 62 (m3/h) 2100 R22) / V/HZ 380/50 x x mm 540x1775x415 x x mm 1250x940x340 kg 55 kg 108	
19		1. 108 2. 3. 3.1 1 2 PVC 3 220V 3 6 380V 5 6 4 3.2 1 108 2 2 5% 3 4 3.3 1 0.8mm 2 3 600 600mm 4 3.4 1 4000-6000K 2 220V-50HZ 3 600MA/DC45-65V 4 20 20 15m 3.5 VR 1 4 2 1300 500 750mm	1

